



Aladdin EasyFit Isolator Guarantee

Terms & Conditions

Products are subject to a 10 or 5 year guarantee that is between NLB Engineering Ltd and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied. This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects and is not applicable where the product has not been fitted in accordance with the fitting instructions in our literature.

The guarantee is subject to the following limitations:

1. The valves are designed for use only on copper or plastic water pipes of either 15mm, 22mm or 28mm (dependent upon version purchased).
2. They must be used within the pressure and temperature limits stated in the technical information table below:

Aladdin EasyFit Isolator Specification	Copper BS EN 1057 (type L & M) 0.7 wall thickness	Copper BS EN 1057 (type K) 1.0 wall thickness	Plastic BS 7291 – PEX, Polybutylene and Multi Layer
15mm			
Max Operating Pressure	16 bar	16 bar	6 bar
Max Operating Temperature	85 deg. C	85 deg. C	82 deg. C
Manufacturer's Warranty	10 yr	10 yr	5 yr
Pipe Size	15mm	15mm	15mm
Max Static Pressure Installs at	16 bar	16 bar	10 bar
Max Dynamic Pressure Installs at	6 bar at 40 lit/min	6 bar at 40 lit/min	6 bar at 40 lit/min

Aladdin EasyFit Isolator Specification	Copper BS 2871 (type X) 0.7 wall thickness	Copper BS EN 1057 (type Y) 1.0 wall thickness	Plastic BS 7291 – PEX, Polybutylene and Multi Layer
15mm Pro			
Max Operating Pressure	16 bar	16 bar	6 bar
Max Operating Temperature	85 deg. C	85 deg. C	82 deg. C
Manufacturer's Warranty	10 yr	10 yr	5 yr
Pipe Size	15mm	15mm & ½"	15mm
Max Static Pressure Installs at	16 bar	16 bar	10 bar
Max Dynamic Pressure Installs at	6 bar at 40 lit/min	6 bar at 40 lit/min	6 bar at 40 lit/min
22mm & ¾" range			
	0.9 wall thickness	1.2 wall thickness	
Max Operating Pressure	16 bar	16 bar	6 bar
Max Operating Temperature	85 deg. C	85 deg. C	82 deg. C
Manufacturer's Warranty	10 yr	10 yr	5 yr
Pipe Size	22mm & 3/4"	22mm	22mm
Max Static Pressure Installs at	16 bar	16 bar	10 bar
Max Dynamic Pressure Installs at	6 bar at 40 lit/min	6 bar at 40 lit/min	6 bar at 40 lit/min
28mm range			
	0.9 wall thickness	1.2 wall thickness	
Max Operating Pressure	16 bar	16 bar	6 bar
Max Operating Temperature	85 deg. C	85 deg. C	82 deg. C
Manufacturer's Warranty	10 yr	10 yr	5 yr
Pipe Size	28mm	28mm	28mm
Max Static Pressure Installs at	16 bar	16 bar	10 bar
Max Dynamic Pressure Installs at	6 bar at 40 lit/min	6 bar at 40 lit/min	6 bar at 40 lit/min

- Damage caused by poor installation technique or accidental damage to the product is not covered by this guarantee The extent of NLB Engineering's liability is limited to the cost of the replacement of the defective item and not to fitting or consequential damages.